

Corrosion-prevention filler for above-ground usage, flanges, tankbottoms, bolts and threats

Features

- Easy to seal uneven, non cleaned or hard-to-access surfaces
- Excellent flow into finest gaps and voids
- Excellent seal against corrosion
- Easy to use
- Long-term protection

Onshore & Offshore

Rehabilitation and new-built pipelines

Underground and above-ground application



STOPAQ®

corrosion
prevention

STOPAQ® 4200

STOPAQ® 4200

The 4200 must be mechanically protected by Wrappingband CZH + suitable mechanical protection



Synthetic a-polar polyolefin

- Easy to apply

Inert and remains a flexible paste

- Excellent bonding to steel, PU, PE

High specific electrical resistance

- Helps to block H₂S gas

Resistant to high temperatures

- Fills the complete space

Does not cure or age

- Environmental friendly
- Non-toxic

Excellent sealing against corrosion

- Minimal surface preparation required

(max. temperature 100°C)

For more info, check the product data sheet at www.STOPAQ.com

DISCLAIMER: In practice, materials, substrates and specific local conditions may differ in such a way that STOPAQ B.V. cannot assume any responsibility for coverage, performance or injuries from use. Liability, if any, is limited to the replacement of products. Intellectual property rights must be respected. All orders and deliveries from STOPAQ B.V. are subject to our Standard Terms and Conditions, registered with the Chamber Of Commerce Groningen under number 02327624.