

# Mechanical Protection Tapes

## Features

- Easy to apply manually & to stretch
- Excellent impact resistance
- Provides extra mechanical strength to corrosion prevention solutions
- Outerwrap PVC: max. 70°C
- Outerwrap PE: max. 80°C
- Outerwrap HTPP: max. 90°C
- Outerwrap PU: max. 95°C

## Onshore & Offshore

Rehabilitation and newbuilt pipelines

Underground and above-ground application



# STOPAQ®

corrosion  
prevention

# STOPAQ® OUTERWRAP

# STOPAQ® OUTERWRAP

UV-resistant flexible mechanical protection tape



## Flexible tape with rubber resin adhesive

- Easy to apply by hand

## High puncture and ageing resistance

- Excellent impact resistance

## Good adhesion strength

- Provides extra strength to corrosion prevention layers

## Suitable for max. 90°C

- Wide service range of use

## Good elongation

- Can be used above-ground exposed to sunlight (excluding PE and HTTP)

For more info, check the product data sheet at [www.STOPAQ.com](http://www.STOPAQ.com)

DISCLAIMER: In practice, materials, substrates and specific local conditions may differ in such a way that STOPAQ B.V. cannot assume any responsibility for coverage, performance or injuries from use. Liability, if any, is limited to the replacement of products. Intellectual property rights must be respected. All orders and deliveries from STOPAQ B.V. are subject to our Standard Terms and Conditions, registered with the Chamber Of Commerce Groningen under number 02327624.